

The easylist package for numbered items

Paul Isambert
zappathustra@free.fr
<http://paulisambert.free.fr>

January 11, 2014

Abstract

This package is designed for typesetting lists of numbered items (like Wittgenstein's *Tractatus* or—more likely—the outline of a work yet to be done) with a single active character acting as the only command. Various options are available to achieve greater control over the general appearance of the list.

Contents

1	Choosing the symbol	2
2	Usage	2
3	Referring to an item	3
4	Options	3
4.1	Parameters affecting the n th counter in an item number	4
	◇ $\text{Start}n$, $\text{Start}n^*$	4
	◇ Mark , $\text{Mark}n$, FinalMark , $\text{FinalMark}n$	4
	◇ Numbers , $\text{Numbers}n$	5
4.2	Parameters affecting numbers and items of the n th level	5
	◇ Hide , $\text{Hide}n$	5
	◇ Style , $\text{Style}n$, Style^* , $\text{Style}n^*$, Style^{**} , $\text{Style}n^{**}$	5
	◇ CtrCom , $\text{CtrCom}n$	6
	◇ Hang , $\text{Hang}n$	6
	◇ Align , $\text{Align}n$	6
	◇ Margin , $\text{Margin}n$	7
	◇ Progressive , Progressive^*	7
	◇ Space , $\text{Space}n$, Space^* , $\text{Space}n^*$	8
	◇ Indent , $\text{Indent}n$	8
	◇ FinalSpace , $\text{FinalSpace}n$	8
5	Predefined styles	8
6	Trouble with boxes	10
7	An example	11
8	Implementation	11
8.1	Declarations and options	11
8.2	Basic recursive definitions	13
8.3	Parameters	15
8.4	Parametric tests	20
8.5	Non-parametric tests	22
	8.5.1 Dimensions	22
	8.5.2 Number denotation	25
	8.5.3 Numbers	25
8.6	Creating items	26

1 Choosing the symbol

Here's what the \LaTeX code with `easylist` in its default usage looks like:

```
\begin{easylist}
§ First proposition.
§§ Interesting comment.
§§§ A note on the comment.
§§§§ Another note.
§§§§§ By the way...
§§§§§§ This is a subsub...-proposition.
§ Let's start something new...
\end{easylist}
```

And it yields:

```
1. First proposition.
  1.1. Interesting comment.
    1.1.1. A note on the comment.
    1.1.2. Another note.
      1.1.2.1. By the way...
        1.1.2.1.1. This is a subsub...-proposition.
2. Let's start something new...
```

(No, the pinky box *isn't* part of the package.)

Now, the section sign § might not be readily accessible on some (most?) keyboards (although it is accessible and useless on French ones). So you can choose another one instead by setting an option when calling the package (§ is default):

```
\usepackage[pilcrow]{easylist} to use ¶
\usepackage[at]{easylist} to use @
\usepackage[sharp]{easylist} to use #
\usepackage[ampersand]{easylist} to use &
```

The selected character is made active between `\begin{easylist}` and `\end{easylist}` and then returns to its initial value. So when using # for instance, just make sure to define new commands outside the `easylist`, or use the `\Activate` and `\Deactivate` commands in your list; as you might have guessed, they make the symbol respectively active and back to its original category. (Ending a list and then beginning a new one will not be noticeable in the final product, so you can interrupt your list to create a new command.) In what follows, I will be using §, but everything applies to other symbols too.¹

2 Usage

First of all, you have to decide how many counters you need. By default, `easylist` creates 10 counters, but you might want more, so just specify a number as an option when calling the package: `\usepackage[50]{easylist}` will create 50 counters. Who knows? this might be useful. You can create as many counters as \TeX allows you to. If you exceed its limit, it'll say it. You can also specify a number below 10, if you want less counters to be created.

The example above says it all, so let's repeat it:

¹You might not be happy with the symbols and maybe you'd like to use another one, or simply have your favorite symbol as default to avoid remembering such a cumbersome name as 'pilcrow'. Here's a simple hack that does the job: select the entire code of the package, and replace all occurrences of § with your symbol. Make sure you won't use it in the list for other purposes, though.

```

\begin{easylis}
§ First proposition.
§§ Interesting comment.
§§§ A note on the comment.
§§§ Another note.
§§§§ By the way...
§§§§§ This is a subsub...-proposition.
§ Let's start something new...
\end{easylis}

```

Your list must be enclosed between `\begin{easylis}` and `\end{easylis}`, which is welcome since a character is made active and active characters are notoriously dangerous. As you might have guessed, one § creates a proposition of the first level, two §'s make a proposition of the second level, and so on down to the fifth level. If you concatenate more §'s than available, you'll get an error message telling you to ask for more and the problematic line will begin with `!!!` instead of numbers. Every sequence of §'s must terminate with a space, otherwise numbers won't be printed.

Two things are worth mentioning. First, note that § automatically creates a new line, so typing your propositions in a row will not affect the result. Hence

```

\begin{easylis} § First proposition.  §§ Interesting comment.  \end{easylis}

```

still yields

```

1. First proposition.
1.1. Interesting comment.

```

Second, when skipping one or more level(s), that(those) level(s) will be numbered 0 (except otherwise specified—see below), as in:

```

\begin{easylis}
§ First proposition.
§§§ A sub-comment to the first proposition.
\end{easylis}

```

which yields:

```

1. First proposition.
1.0.1. A sub-comment to the first proposition.

```

That's it. The following sections deal with labelling and referring and layout options, but for basic purpose you don't need more than that. Predefined style, available with `\begin{easylis}[<Style>]`, are treated in section 5.

3 Referring to an item

You can use L^AT_EX's `\label`, `\ref` and `\pageref` to refer to an item. The `\label` can appear anywhere in the text of the item (affecting only `\pageref`) but if you put it after the row of §'s, make sure there's a space in between, otherwise § won't fire, as mentioned above. The output of `\ref` is the counters of the item referred to with their original denotation and punctuation but not their original `Style` or `CtrCom` (see below), that is they adopt style where `\ref` is called. Only counters that have not been hidden will appear.

4 Options

Several parameters are available to achieve a finer control over the final output. The general command is `\ListProperties(key=value,key=value...)`, where `key` is a parameter. `ListProperties` affects all *subsequent* items and all subsequent lists, wherever it is issued. If you want to set the parameters back to

default, use `\NewList`, which can also have an argument (between parentheses like `\ListProperties`) and will then function as `\ListProperties` if you want to specify again a parameter. Note that you don't need to put all your parameters in the same `\ListProperties`: several `\ListProperties(key=value...)` have the same effect as a big `\ListProperties` with all parameters at once. By definition, this is not the case for `\NewList`—which, by the way, I'm using in all examples here, although I show `\ListProperties` just to make you believe in the illusion of a stand-alone list...

Parameter n affects the n th counter (e.g. 5 in 14.5.22 is the second counter) or the item of the n th level (e.g. 14.5.22 is a counter of the third level). I think there isn't much room for ambiguity, and at least the context will make clear what I'm talking about—and if you're still uncertain, well, just try the parameter!

If a value contains a comma or a closing parenthesis, you should enclose it between braces or `easylist` will take them to be delimiters. For instance, if you want a closing parenthesis to be `FinalMark` (see below), say `\ListProperties(FinalMark={})`. And if you want to put a `framebox` anywhere, say for instance `\ListProperties(Style2*={\framebox(5,5){}})`.

4.1 Parameters affecting the n th counter in an item number

Start n
Start n *

- `Start n =<Number>` makes the n th counter start at `<Number>`, if and only if it immediately precedes an item containing that counter, otherwise it is useless.
- `Start n *=<Counter>` makes the n th counter dependent on `<Counter>`, where `<Counter>` is an external counter, like `\thesection`. The counter cannot be controlled anymore and stubbornly follows `<Counter>`. To make it back to normal, say `Start n *=NA`, which is of course default.

```
\begin{easylist}
\ListProperties(Start1*=\thesection,Start2=17)
§ First proposition.
§§ Numbering doesn't work.
\ListProperties(Start2=17)
§§ This is better.
§ Hey, I can't move on!
§ I must be stuck to an external counter!
\ListProperties(Start1*=NA)
§ Okay, it works again.
\end{easylist}

4. First proposition.
4.1. Numbering doesn't work.
4.17. This is better.
4. Hey, I can't move on!
4. I must be stuck to an external counter!
5. Okay, it works again.
```

Mark
Mark n
FinalMark
FinalMark n

- `Mark=<Punctuation>` sets the punctuation of all counters to `<Punctuation>`.
- `Mark n =<Punctuation>` sets the punctuation of the n th counter to `<Punctuation>`.
- `FinalMark=<Punctuation>` sets the punctuation of the final counter, if specified, for all items. To unspecify it without using `\NewList`, say `FinalMark n =NA`.
- `FinalMark n =<Punctuation>` sets the punctuation of the last (i.e. the n th) counter of the n th item. To unspecify it without using `\NewList`, say `FinalMark n =NA`.

The difference between `Mark(n)` and `FinalMark(n)` is that the latter supersedes the former at the end of the counters numbering an item. In case `FinalMark(n)` is set to `NA`, then `Mark(n)` is used in all positions. The default punctuation mark is a full stop, and `FinalMark` is unspecified (so all item numbers end with a full stop by default).

In the following example, note that `=` followed by nothing is understood as a normal value, albeit empty, and that specifying `FinalMark3` *after* `FinalMark` makes the former win. If `FinalMark3` had appeared *before* `FinalMark`, then its value would have been superseded. It works the same for all the parameters that follow.

There's a final caveat: if you want fixed spaces as marks, you shouldn't use L^AT_EX's `\hspace` but T_EX's original `\hskip`. The former makes it all wrong, and I don't really know why (it doesn't stand being the replacement text of a macro defined with `\edef` or `\xdef`). You may not be used to `\hskip`, but it's very simple. Instead of `\hspace{1cm}`, for instance, say `\hskip 1cm`.

```
\ListProperties(Mark=.,FinalMark=,FinalMark3={})}
1 The world is all that exists...
1.1 ... said Ludwig to Lizzie...
1.1.1) ... but she wasn't listening.
```

Numbers
Numbersn

- **Numbers**=*<Number denotation>* sets the way all counters are printed.
- **Numbersn**=*<Number denotation>* sets the way the *n*th counter is printed. Here are the admissible values:

```
r for lower case roman numerals;
R for upper case roman numerals;
l for lower case letters;
L for upper case letters;
z for Zapf's Dingbats;
a for arabic numbers, which are the default value.
```

Note that if you choose letters for a given counter, it should not exceed 26, or T_EX will complain—and you'll have no number at all. Since I think that using letters with more than, say, 10 items, is ill-advised, I didn't overcome that limitation.

```
\ListProperties(Numbers2=R,Numbers3=L,Numbers4=r,Numbers5=l,Numbers6=z)
1. I...
1.I. ... really...
1.I.A. ... like...
1.I.A.i. ... numbers...
1.I.A.i.a. ... however...
1.I.A.i.a.☞. ... they are printed.
```

4.2 Parameters affecting numbers and items of the *n*th level

Hide
Hiden

- **Hide**=*<Number>* hides the first *<Number>* counters for all items. It isn't very useful unless you want all counters to be hidden for all items, that is you want lists of unnumbered items, in which case you may say **Hide**=100 (or **Hide**=10000 if you have more than 100 counters!).
- **Hiden**=*<Number>* hides the first *<Number>* counters for items of the *n*th level. This is more useful. If *<Number>* > *n*, then nothing is printed. Note that if you refer to an item with hidden numbers, those will not appear when referring to the item with `\ref`. See the example below.

```
\ListProperties(Hide2=1,Hide3=2,Progressive*=.5cm,Numbers3=1,
Numbers4=r,FinalMark3={})}
1. Now, what's the difference with enumerate? asks Leslie.
1. Frankly, I don't know, Don answers.
a) Should have made it proprietary.
1.1.a.i. And suddenly all counters reappear... This is ugly! they both ex-
claim, but they cannot help noticing that referring to the previous item with
\ref yields a).
```

Style
Stylen
Style*
Stylen*
Style**
Stylen**

- **Style**=*<Format>* sets the style of counters and text for all items.
- **Stylen**=*<Format>* sets the style of counters and text for items of the *n*th level.
- **Style***=*<Format>* sets the style of all counters.
- **Stylen***=*<Format>* sets the style of the counters of items belonging to the *n*th level.
- **Style****=*<Format>* sets the style of all item texts.
- **Stylen****=*<Format>* sets the style of the texts of items belonging to the *n*th level.

Since numbers and texts are enclosed in groups, *<Format>* can safely be a command such as `\bfseries` or `\itshape`, etc., or even `\color{green}` of the `xcolor` package. The no-star version interacts freely with the other two (up to (L)T_EX's font limitations).

Those parameters are actually placeholders in front of the counter or the text of the item (or both in case of **Style**), so you can use them to add nice symbols, for instance.

The default style is the style of your document.

```
\ListProperties(Style=\color{blue},Style1*=\bfseries,
Style2*=\itshape,Style1**=\scshape$\bullet$,
Style1***=\diamond$,Style3**=\Rightarrow$,Hide3=3)
```

1. • A FUNDAMENTAL PROPOSITION.

1.1. ◊ An essential comment.

⇒ First...

⇒ Then...

⇒ And we should not forget...

CtrCom
CtrComn

- **CtrCom**=*<Command>* makes *<Command>* into a command whose argument is the counters of all items.
- **CtrComn**=*<Command>* makes *<Command>* into a command whose argument is the counters of items of the *n*th level.

Note that *<Command>* can only be a command taking one token (i.e. possibly a group) as its last argument. Only the bare command must be issued when specifying the parameter. In the following example, `CtrCom=\colorbox{pink}` thus means `CtrCom=\colorbox{pink}{COUNTERS}`.

```
\ListProperties(CtrCom=\fbox,CtrCom3=\colorbox{pink})
```

1. A box is a box is a box...

1.1. ... said Gertie to Jim...

1.1.1. ... who was looking for Leopold.

Hang
Hangn

- **Hang**=*<Boolean>* lets all item texts hang from their counters if *<Boolean>* is true.
- **Hangn**=*<Boolean>* let all item texts of level *n* hang from their counters if *<Boolean>* is true.

If you don't want texts to hang, set *<Boolean>* to false, or F, or RDNZL or even True for that matter, i.e. anything but true. By default, no text hangs from its counter.

If you specify **Margin** or **Progressive** (see below), the counter will be at the specified distance and the text of the item will be at that distance plus the width of the counter. If you specify **Indent** (see below again), the first paragraph won't be indented.

```
\ListProperties(Margin1=1cm,Hang1=true,Indent1=.5cm)
```

1. I'm a nice item with a margin of 1cm for my counter and, well, 1cm plus something else for me.

Here I have an indent because I'm a brave new paragraph.

```
\ListProperties(Hang1=false)
```

2. Hey! I'm not hanging anymore! I just have a 1cm margin! And I'm already indented!

Align
Alignn

- **Align**=*<keyword or dimension>* aligns all item texts at the same level for all levels.
- **Alignn**=*<keyword or dimension>* aligns all item texts of the *n*th level.

This needs an explanation. Item numbers don't have the same width, even if they belong to the same counter. For instance, the first item of the first level has 1 as its number, while the 33rd one of the same level has 33, and obviously 33 is a wider expression than 1. So the corresponding item texts won't start at the same horizontal distance, i.e. they won't be aligned. And if texts hang from their counters, the entire left margin will be unaligned, which might be pretty ugly.

This parameter is meant to avoid such a situation. If *<keyword>* is **move**, then the item number will be moved to the left if it is too large (as in the `enumerate` environment). If *<keyword>* is **fixed**, the **FinalSpace** (see below), i.e. the space between the item number and the item text, will be shrunk (or stretched) accordingly (as in a table of contents). If it is reduced to nothing and the counter is still too wide, then the counter will spread on the text and you'll get a warning; then you should increase **FinalSpace** so the *first* counter will be larger and the problematic one will have more room. In both cases, the reference width is the width of the first item counter (of the adequate level, of course) that `easylist` meets *after* the parameter is set. It is very likely to be 1, thus a narrow counter. Finally, if you use a *<dimension>* instead of a keyword, it has the same effect as **fixed**, except that the reference width is not the width of the first counter of that level but the specified dimension. **FinalSpace** then becomes useless.

Set *<keyword>* to anything but **fixed** and **move** to turn off this parameter, which by default is not in use. Note that items belonging to different levels aren't aligned with one another.

```

\ListProperties(Hang=true,Margin=1cm,
FinalSpace=2em)
    1. Here is the first item of my very uninteresting
        yet very convenient list.
    1000. Here's the 1000th one which obviously isn't
           aligned with what precedes, although both
           are on the same level.

\ListProperties(Hang=true,Margin=1cm,
Align=fixed,FinalSpace=2em)
    1. Here is the first item of my very uninteresting
        yet very convenient list.
    1000. Here's the 1000th one which obviously is
           aligned with what precedes. Fortunately,
           FinalSpace was wide enough.

\ListProperties(Hang=true,Margin=1cm,
Align=move,FinalSpace=2em)
    1. Here is the first item of my very uninteresting
        yet very convenient list.
    1000. Here's the 1000th one which is also aligned
           with what precedes, but it would have run out
           of the box if Margin hadn't been taken care
           of.

\ListProperties(Hang=true,Margin=1cm,Align=2cm)
    1. Hey, my counter is 2cm wide.
    1000. Mine too.

```

A NOTE ON DIMENSIONS: the following parameters take *<Dimensions>* as values. However, those dimensions should be specified explicitly (e.g. `\ListProperties(Margin=2cm)`) or with a command (e.g. `\newcommand{\mydimension}{2cm}` and then `\ListProperties(Margin=\mydimension)`), but you should not directly use real TeX dimensions defined with `\newdimen` (or L^AT_EX's `\newlength`), etc. In case you want such dimensions here, you have to prefix them with `\the`. So if you have defined a dimension `\mydimen`, `ListProperties(Margin=\the\mydimen)` is ok, but not `\ListProperties(Margin=\mydimen)`. This may sound paradoxical, and indeed it is, but `easylist` runs some tests on the parameters before TeX gets crazy (you want to avoid 10 error messages when you have 10 counters), and in order to test a dimension, it has to be readable, hence `\the`.

Margin
Marginn

- `Margin=<Dimension>` sets the distance from the left margin at which all items should start.
- `Marginn=<Dimension>` sets the distance from the left margin at which items of the *n*th level should start.

A negative value doesn't move the left margin to the left, but indents the right margin.

```

\ListProperties(Margin2=3ex,Margin3=6ex,Margin4=9ex,
Margin5=12ex)
1. First proposition.
  1.1. Interesting comment.
    1.1.1. A note on the comment.
    1.1.2. Another note.
        This is fascinating. We can start a new paragraph at any
        level and it remains where it should be.
      1.1.2.1. By the way...
        1.1.2.1.1. This is a subsub...-proposition.
2. Let's start something new...

```

Progressive
Progressive*

- `Progressive=<Dimension>` sets the margin of all items to a distance depending on their level. Namely, items of the *n*th level have a margin of $n \times \langle Dimension \rangle$.
- `Progressive*=<Dimension>` does the same, except that items of the *n*th level have a margin of $n \times \langle Dimension \rangle - \langle Dimension \rangle$. This means that items of the first level will be at the current margin and that the progressive indentation will start at the second item.

Thus the previous example could have been typeset with:

```
\ListProperties(Progressive*=3ex)
1. First proposition.
  1.1. Interesting comment.
    1.1.1. A note on the comment.
    1.1.2. Another note.
      This is fascinating. We can start a new paragraph at any
      level and it remains where it should be.
        1.1.2.1. By the way...
          1.1.2.1.1. This is a subsub...-proposition.
2. Let's start something new...
```

You can still specify `Margin` (*after Progressive*) if you want some items to be at a specified distance.

Space
Space n
Space*
Space n *

- `Space=<Dimension>` sets the vertical space between items of a different level.
- `Space n =<Dimension>` sets the vertical space between items of the n th level and previous items belonging to another level.
- `Space*=<Dimension>` sets the vertical space between items of the same level.
- `Space n *=<Dimension>` sets the vertical space between items of the n th level and previous items belonging to the same level.

This space is added to the normal space between two lines. You can use a negative value if you want to compact your list.

```
\ListProperties(Space2=1cm,Space2*=.5cm)
1. Innocent item.

1.1. What a space! It must be Space2!

1.2. This one is less impressive. It must be Space2*.
```

Indent
Indent n

- `Indent=<Dimension>` sets the indentation of all paragraphs.
- `Indent n =<Dimension>` sets the indentation of paragraphs belonging to items of the n th level.

```
\ListProperties(Indent2=2cm,Margin2=1cm)
1. Here is an unaffected item.
    1.1. Here is a paragraph. Its text
        is totally silly. But it exhibits a nice indenta-
        tion.
        Here's a new paragraph, under
        the same number. Its text is still silly, but
        it still has a nice indentation too.
```

FinalSpace
FinalSpace n

- `FinalSpace=<Dimension>` sets the distance between the item number (more precisely, the last mark) and the text for all items. Default is `.3em`.
- `FinalSpace n =<Dimension>` sets the distance between the item number (more precisely, the last mark) and the text for items of the n th level. This may not be very useful, except when adjusting it to meet the requirements of alignment.

In case you set the `Align` parameter to `fixed`, `FinalSpace` may be shrunk or stretched.

```
\ListProperties(FinalSpace2=1cm)
1. The following item wants to be seen.
  1.1. Yes I do.
```

5 Predefined styles

You can load some predefined styles with `\begin{easylis}[<Style>]`. They simply issue `\NewList` with some special values. You can still add `\ListProperties` to modify them further, and you can still interrupt your list and start it again later, and you don't have to specify `\begin{easylis}[<Style>]`:

`\begin{easylist}` is enough, since it will inherit the properties of the previous one (if it hasn't been `\NewList`'ed, of course).

• `tractatus` is an imitation of Wittgenstein's *Tractatus Logico-Philosophicus*. It's quite simple: `Mark1` is turned to a dot, and all other marks are turned off.

```
1. The world is all that exists.
1.1 If something doesn't exist, it doesn't belong to
the world.
1.11 Of something that doesn't exist, we should not
speak.
2. I won't speak of things that don't exist.
2.1 Although they have some appeal to me.
2.10001 I really can't resist.
```

• `checklist` has no numbers, only check boxes, items are indented according to their levels, and the style of the first level is `\bfseries`.

Things to do

```
 Finish the easylist package
 Find new predefined styles
 Comment the code
 Avoid being verbose and making dumb jokes
to hide weaknesses
 Tidy up the room
```

• `booktoc` roughly emulates a table of contents according to the `book` class (without page numbers, of course). Items of the first level are formatted like parts, and so on. Items of the seventh level and higher are not formatted at all.

I My part

1 My chapter

1.1 My wonderful section

1.1.1 My tremendous subsection

1.1.1.1 My very exciting subsection

1.1.1.1.1 My delicate paragraph

1.1.1.1.1.1 My secret subparagraph where everything is unveiled and which goes to the end of the line to show its hanging from the counter

2 My second chapter

• `articletoc` does the same for the `article` class. Items of the first level are sections, etc. Items of the fifth level and higher are not formatted.

1 A very interesting section

1.1 A subsection that will explain great theories

1.1.1 Here we find a proof

1.1.1.1 And a corollary here

1.1.1.1.1 This paragraph seems really cool

• `enumerate` mimicks the `enumerate` environment as defined in the \LaTeX base and `article` class. Items of the fifth level and higher aren't formatted.

```

1. I have something to say...
  (a) But I don't know if I can...
      i. This is enumerate made easy...
          A. Oh yeah, you can spot some differences too,
              maybe in the separation between items...
(Two hours later)
200. Now that we've come thus far, let's study alignment of items
    in this emulated enumerate environment.

```

• `itemize` does the same for the `itemize` environment.

```

• Hey, this is a bullet.
  - And this is a dash.
    * Here we have an \ast (don't forget the $'s!).
      · And finally a \cdot, in case you didn't know.

```

6 Trouble with boxes

Active characters, as is well known, are nasty beings, and it's hard to keep them activated all the way down. That's why the `easylist` environment in its present state won't work in boxes. That is

```

\fbbox{%
\begin{easylist}
§ First proposition.
\end{easylist}}

```

will print:

```

§ First proposition.

```

where § is the normal value of § (in T1 font encoding). Lists in boxes aren't that common (except for this document), but such a limitation is always annoying. The solution is to make active the character you've chosen to create items just before the box and then turn it back to its initial value. For that purpose, `easylist` has the two commands `\Activate` and `\Deactivate`. So here's what you'll do:

```

\Activate
\fbbox{%
\begin{easylist}
§ First proposition.
\end{easylist}}
\Deactivate

```

and you'll get:

```

1. First proposition.

```

Unfortunately, this has to be issued for every box. That is, the following code won't work (even if you surround your command definition with `\Activate` and `\Deactivate`—I told you that active characters were nasty):

```

\newcommand{\myfbbox}[1]{\Activate\fbbox{#1}\Deactivate}
\myfbbox{%
\begin{easylist}
§ First proposition.
\end{easylist}}

```

Finally, for some boxes, as for instance the `\fbbox` above, a `\NewList` should be issued at the beginning of the list. Don't ask me why. Instead, avoid `\fbboxes`.

7 An example

Now, it so happened that French writer Jacques Roubaud published a book named **La Dissolution** just as I released the first version of this package (although the book was written in 2000). He uses MS word and has some troubles with the numbered items of which his text is made. I don't know if he knows T_EX (he's a retired professional mathematician, so who knows?), but anyway here's an excerpt from the book as a tribute to that coincidence. It's in French.

```
\NewList(Style*=\footnotesize,Style3=\color{red},Style4=\color{blue!60!black})
\ListProperties(Style5=\color{green!60!black},Style6=\color{violet})
\ListProperties(Style7=\color{yellow!50!brown},Style8=\color{gray})
\ListProperties(Start1=70,Start2=6,Progressive*=2em,Mark= )
```

70 6 Après une heure environ de lecture de choses à lire et de lecture de paysage

70 6 1 m'amenant à découvrir que le Châlons traversé par le train ne se nommait plus, comme dans mon souvenir d'écolier, -sur Marne, mais -en Champagne, réforme onomastique récente qui m'avait jusqu'alors échappé, et avait vraisemblablement obligé les autorités municipales à un intense "lobbying"

70 6 1 1 il y aura bientôt un Villefranche-en-Beaujolais-nouveau, si Mâcon laisse faire

70 6 1 2 je vérifie, à tout hasard, que Reims n'est pas devenu Reims-en-Champagne

70 6 1 2 1 aucune ville X n'a choisi de se renommer "X en Champagne Pouilleuse"

70 6 1 2 1 1 laquelle a été baptisée, pendant que je ne regardais pas, "Champagne crayeuse"

70 6 1 2 1 1 1 rebaptême qui a vraisemblablement obligé les autorités de quelques groupements d'autorités municipales à un intense "lobbying"

70 6 1 2 1 1 1 1 les progrès du P.C. sont globaux comme l'économie du même adjectif

(© Éditions Nous)

8 Implementation

I'm not used to DocStrip so I input the code by hand with the `fancyvrb` package. Gaps in line numbering correspond to blank lines in the package. Besides, I'm pretty talkative, so I put the code in red. It will be easier to skip comments.

8.1 Declarations and options

After some commented-out information, here are the usual declarations:

```
17 \NeedsTeXFormat{LaTeX2e}
18 \ProvidesPackage{easylist}[2014/01/11 v.1.4 Numbered items with a single command.]
```

To process options, we already need conditionals and counts. The first four conditionals and the first count will be used in options, while the remaining conditional and counts are used in the following tests. We also define a convenient shorthand.

```
20 \makeatletter
21
22 \newif\ifPilcrow
23 \newif\ifAt
24 \newif\ifSharp
25 \newif\ifAmpersand
26 \newif\ifDubiousFigure
27
```

```

28 \newcount\el@CounterTotal
29 \el@CounterTotal10
30 \newcount\el@Scratch
31 \def\el@Advance#1{\advance#1 by 1\relax}

```

The `\el@NumberCheck` test is a basic token-by-token test that checks whether a sequence is made of numbers, which unfortunately have no category code of their own. The command takes the next character, compares it to 0, then 1, up to 9, etc. until it matches; if it doesn't the sequence is not a number and `\DubiousFiguretrue` is output.

First, `\el@NumberCheck` looks whether the next character is `?`, the terminator, in which case the control counter is set to 0, `\e@synext` (called at the end of the command to create recursion) is deactivated and the command comes to an end. So we can write `\el@NumberCheck 2563?` and 2563 will be tested.

```

33 \def\el@NumberCheck#1{%
34 \expandafter\if#1?%
35   \el@Scratch0
36   \def\e@synext##1{\relax}%

```

Then, if the argument is not `?`, but the control counter has reached 10, then the argument is not a number (all figures have been exhausted). The counter is set to 0, the sequence is said doubtful and the rest of it is discarded:

```

37 \else
38   \ifnum\el@Scratch=10
39     \el@Scratch0
40     \def\e@synext##1?{\relax}%
41     \DubiousFiguretrue

```

If all figures have not been tried, the argument is compared to the present one, which is the value of the control counter. If it matches, the counter is reset and the command proceeds to the next character. If not, the counter is stepped and the command is called on the same argument:

```

42 \else
43   \expandafter\if#1\the\el@Scratch
44     \el@Scratch0
45     \def\e@synext##1{\el@NumberCheck}%
46   \else
47     \el@Advance\el@Scratch
48     \let\e@synext\el@NumberCheck
49   \fi
50 \fi
51 \fi\e@synext{#1}}

```

Now we can declare options. When it comes to choosing the symbol, they simply makes some conditional true. The conditional will be used at the end of the package, when we define the environment.

```

53 \DeclareOption{pilcrow}{\Pilcrowtrue}
54 \DeclareOption{at}{\Attrue}
55 \DeclareOption{sharp}{\Sharptrue}
56 \DeclareOption{ampersand}{\Ampersandtrue}

```

The remaining (undeclared) option is checked and if it's a valid number (if it passes the test above), then `\el@CounterTotal`, which tells the entire package how many counters, parameters, etc., must be created, is set to its value:

```

57 \DeclareOption*{%
58 \expandafter\el@NumberCheck\CurrentOption?%
59 \ifDubiousFigure
60   \PackageError{easylis}{%
61   ^^J==> 'CurrentOption' is not a valid number (in package options).
62   ^^J==> It is ignored and there are only 10 counters}{}%
63 \else
64   \el@CounterTotal\CurrentOption
65 \fi\DubiousFigurefalse}
66 \ProcessOptions\relax

```

We need two more counters for the rest of the package (well, for now):

```
68 \newcount\el@ControlCounter
69 \el@ControlCounter1
70 \newcount\el@CounterLevel
71 \el@CounterLevel1
```

8.2 Basic recursive definitions

Since the number of counters depends on `\el@CounterTotal`, I can't create them in advance, so I designed recursive commands whose purpose is to create other commands in a given amount. The general trick is quite basic: simply use `\easynext` at the end of the command, which is `\let` to the command itself if the desired quantity (specified by `\el@CounterTotal`) has not been reached yet, and to `\relax` otherwise.

First, `\Generic@Counter` creates as many counters as needed. They are named `List1`, `List2`, `List3`, etc., and they are respectively the first, second, third, etc. counter of the final output. It's so simple that we don't need `\easynext` to create tail recursion. We simply `\expandafter` the command itself at the end of the conditional, so it jumps the `\fi`.

```
73 \def\el@GenericCounter{%
74 \ifnum\el@ControlCounter>\el@CounterTotal
75   \el@ControlCounter1
76 \else
77   \newcounter{List\the\el@ControlCounter}%
78   \el@Advance\el@ControlCounter
79   \expandafter\el@GenericCounter
80 \fi}
81
82 \el@GenericCounter
```

`\Generic@Def` creates the commands that define parameters of the counters, that is `Margin`, `Style`, and so on, once again according to `\el@CounterTotal`.

Basically, `\Generic@Def [A]{B}{C}` will create commands `\B1A`, `\B2A`, `\B3A`, etc., with the definition `C`. The optional argument is needed to handle stars as in `\Start1*`, `\Style2*`, `\Style2**`, etc. (Yes, it would have been much simpler and somewhat more coherent to define and use `\Style**2` instead of `\Style2**`, for instance. But `\Style**2` does not please my eye.) Of course, `\Style2**` is not a valid \TeX command, since it does not contain only category 11 characters (i.e. letters), but `\csccommand Style2**\endcsname` is and I use it throughout the package.

First, we check whether there still needs commands. If not, i.e. if the control counter is higher than the number of required levels, then the control counter is reset and the command does not reiterate:

```
84 \newcommand{\el@GenericDef}[3] []{%
85 \ifnum\el@ControlCounter>\el@CounterTotal
86   \def\easynext[##1]##2##3{\relax}%
87   \el@ControlCounter1
```

If there still needs commands, then one is created whose name depends on the value of the control counter. The `\def` is global (`\gdef`) because the `easylist` environment is made of concatenated groups; hence, if `\ListProperties` is called between `\begin{easylist}` and `\end{easylist}`, the parameters so defined would be stuck to their groups. Moreover, the `\gdef` is prefixed with `\expandafter`, otherwise it would try to define `\csname`, which would be a very bad idea. Globality and delay of `\def` are pervasive in this package.

```
88 \else
89   \expandafter\gdef\csname #2\the\el@ControlCounter#1\endcsname{#3}%
```

Once the command is created, the control counter is stepped and the command reiterates:

```
90   \el@Advance\el@ControlCounter
91   \let\easynext\el@GenericDef
92 \fi
93 \easynext[#1]{#2}{#3}}
```

Now we create the default values of the parameters. These are important even if they're empty, because in what follows we'll look for invalid parameters as undefined commands. The command `\el@PreviousItem` is used for the `Space` parameter. It records the level of the previous item, and since the first list has no previous item, it is set to 0. `NA` is the value of a parameter which has to be discarded.

```

95 \def\el@PreviousItem{0}
96 \el@GenericDef{FinalMark}{NA}
97 \el@GenericDef{Mark}{.}
98 \el@GenericDef{Margin}{0cm}
99 \el@GenericDef{Numbers}{a}
100 \el@GenericDef{Style}{}
101 \el@GenericDef[*]{Style}{}
102 \el@GenericDef[**]{Style}{}
103 \el@GenericDef{Indent}{0cm}
104 \el@GenericDef{Start}{NA}
105 \el@GenericDef[*]{Start}{NA}
106 \el@GenericDef{CtrCom}{}
107 \el@GenericDef{Space}{0cm}
108 \el@GenericDef[*]{Space}{0cm}
109 \el@GenericDef{Hide}{0}
110 \el@GenericDef{Hang}{false}
111 \el@GenericDef{FinalSpace}{.3em}
112 \el@GenericDef{Align}{false}

```

The `Progressive(*)` parameter is different, since it creates a different definition for each command (namely the `Margin` command), so it can't use `\el@GenericDef`. It sets the `Margin` of each item to $n \times \langle Dimension \rangle$ where $\langle Dimension \rangle$ is the argument of the command and n is the level of the item. The starred version simply subtracts one argument (which is a dimension) to each `Margin`, which is thus set to $n \times \langle Dimension \rangle - \langle Dimension \rangle$, and so items of the first level stay at the current margin.

First we need a new conditional and a new dimension:

```

114 \newif\ifProgressiveStar
115 \newdimen\el@ProgressiveDimension

```

`Progressive` calls `\el@ProgressiveMargin` and `Progressive*` calls `\el@ProgressiveMargin*`. It's the same command, but with a different value for the conditional.

```

117 \def\el@ProgressiveMargin{%
118 \ifstar
119 {\ProgressiveStartrue\el@ProgressiveM@rgin}%
120 {\ProgressiveStarfalse\el@ProgressiveM@rgin}}

```

`\el@ProgressiveM@rgin` does the real job. First, as usual, it checks whether there are enough commands, in which case it resets and stops:

```

122 \def\el@ProgressiveM@rgin#1{%
123 \ifnum\el@ControlCounter>\el@CounterTotal
124 \def\easynext##1{\relax}%
125 \el@ControlCounter1

```

If a command must be created, it sets the dimension to the value of the argument and multiply it by the level of that command:

```

126 \else
127 \el@ProgressiveDimension#1%
128 \multiply\el@ProgressiveDimension by \el@ControlCounter

```

Then, if in the starred version, it subtracts one argument to the dimension:

```

129 \ifProgressiveStar
130 \advance\el@ProgressiveDimension by -#1%
131 \fi

```

The `Margin` of the level is set to the value of the dimension. The definition is global for the same reason as above and immediate (`\xdef`) because the value of the dimension is changed at each iteration of `\el@ProgressiveM@rgin`, so we want to store it beforehand. Finally, the dimension is stringed with `\the` because we want to be able to test it (dimensions are unanalyzable tokens). Actually, it has already been tested when the user called the `Progressive` parameter. But since it becomes the value of the `Margins`, and since these are tested after each `\ListProperties`, we want it to be so.

```

132 \expandafter\xdef\curname Margin\the\el@ControlCounter\endcurname{%
133 \the\el@ProgressiveDimension}%

```

Finally, we step the control counter and reiterate:

```

134   \el@Advance\el@ControlCounter
135   \let\easynext\el@ProgressiveM@argin
136 \fi
137 \easynext{#1}}

```

8.3 Parameters

In the first (nonrecursive) version of this package, I used the `keyval` package to set the parameters. But I was not able to use `keyval` pairs into recursive definitions, so I had to create such pairs myself. This proved rather easy, albeit fastidious and ugly—because the package has to check parameters to process them. I’m nonetheless very happy with that because I was able to tailor more precise tests.

`\ListProperties(Arg)` calls `\el@ListProperties` on ‘A=A,Arg,Z=Z,’ with ‘A=A’ to avoid troubles in case of an empty `\ListProperties()` and ‘Z=Z’ as a terminator. Once parameters have been set, it runs some tests on the testable arguments, described below. The values of `Style` or `Mark` cannot be tested, of course, because they’re so diverse.

```

139 \def\ListProperties(#1){%
140 \el@ListProperties A=A,#1,Z=Z,%
141 \el@GenericNumberCheck{Hide}%
142 \el@GenericNumberCheck{Start}%
143 \el@GenericNumberCheck[*]{Start}%
144 \el@GenericLetterCheck
145 \el@GenericUnitSearch{Margin}%
146 \el@GenericUnitSearch{Indent}%
147 \el@GenericUnitSearch{Space}%
148 \el@GenericUnitSearch[*]{Space}%
149 \el@GenericUnitSearch{FinalSpace}}

```

`\NewList` calls `\el@NewList` and then `\ListProperties` if the next character is an opening parenthesis.

```

151 \def\NewList{%
152 \@ifnextchar(%
153   {\el@NewList\ListProperties}%
154   {\el@NewList}}

```

`\el@NewList` simply sets all parameters back to default and reset all counters. `\el@ResetCounters` (which needs setting `\el@ControlCounter` to 0) is described in section 8.6. Don’t worry for `\el@ControlCounter` set to 0, the tests below bring it back to 1, its default value.

```

156 \def\el@NewList{%
157 \el@ControlCounter0
158 \el@ResetCounters
159 \gdef\el@PreviousItem{0}%
160 \el@GenericDef{FinalSpace}{.3em}
161 \el@GenericDef{FinalMark}{NA}%
162 \el@GenericDef{Mark}{.}%
163 \el@GenericDef{Margin}{0cm}%
164 \el@GenericDef{Numbers}{a}%
165 \el@GenericDef{Style}{}%
166 \el@GenericDef[*]{Style}{}%
167 \el@GenericDef[**]{Style}{}%
168 \el@GenericDef{Indent}{0cm}%
169 \el@GenericDef{Start}{NA}%
170 \el@GenericDef[*]{Start}{NA}%
171 \el@GenericDef{CtrCom}{}%
172 \el@GenericDef{Space}{0cm}
173 \el@GenericDef[*]{Space}{0cm}%
174 \el@GenericDef{Hide}{0}%
175 \el@GenericDef{Hang}{false}%
176 \el@GenericDef{Align}{false}}

```

Finally, we need keywords to identify parameters without numbers, like `Style`, and some values:

```

178 \def\el@MarginTest{Margin}
179 \def\el@MarkTest{Mark}
180 \def\el@FinalMarkTest{FinalMark}
181 \def\el@NumbersTest{Numbers}
182 \def\el@IndentTest{Indent}
183 \def\el@StyleTest{Style}
184 \def\el@CtrStyleTest{Style*}
185 \def\el@ParStyleTest{Style**}
186 \def\el@CounterCommandTest{CtrCom}
187 \def\el@ProgressiveTest{Progressive}
188 \def\el@ProgressiveStarTest{Progressive*}
189 \def\el@StartTest{Start}
190 \def\el@StartStarTest{Start*}
191 \def\el@SpaceTest{Space}
192 \def\el@SpaceStarTest{Space*}
193 \def\el@HideTest{Hide}
194 \def\el@HangTest{Hang}
195 \def\el@FinalSpaceTest{FinalSpace}
196 \def\el@AlignTest{Align}
197 \def\el@True{true}
198 \def\el@False{false}
199 \def\el@Fixed{fixed}
200 \def\el@AlreadyFixed{alreadyfixed}
201 \def\el@Move{move}
202 \def\el@AlreadyMoved{alreadymoved}

```

Here are some shorthands. `^^J` is the character creating a new line and `==>` is simply a useless decoration.

```

204 \newcommand{\el@Error}[4] []{%
205 \PackageError{easylist}{^^J==> ‘#3’ is not a valid #4 (#2=#3). It is ignored#1}{}}
206 \def\el@DimenError#1#2{%
207 \el@Error[.^^J==> Note that true TeX dimensions should be prefixed with%
208 ^^J==> \string\the\space in \string\ListProperties]{#1}{#2}{dimension}}

```

And here comes the ugly definition. Most of the conditionals aren't indented because they amount to exclusive cases, and it's ugly enough. The command takes two parameters delimited by `=` and a comma at the end (i.e. `Parameter=Value,`), does a lot of testing and if everything is ok assigns `Value` to `\Parameter`. Roughly speaking.

First we reset all conditionals and names issued by tests (see below):

```

210 \def\el@ListProperties#1=#2,{%
211 \DubiousFigurefalse
212 \DubiousLetterfalse
213 \DubiousNumberfalse
214 \DubiousParameterfalse
215 \Pointfalse
216 \Signfalse
217 \def\el@Parameter{}%
218 \def\el@ParameterNumber{}%

```

Then we set the default value of tail recursion and store the names of the parameter and the value:

```

219 \let\easynext@Properties\el@ListProperties
220 \def\el@TempParameter{#1}%
221 \def\el@TempValue{#2}%

```

If the parameter is equal to `Z`, we redefine tail recursion as `\relax` so the process comes to an end. If the parameter is `A`, we simply go on, since `A` is just a placeholder.

```

222 \if#1Z%
223 \let\easynext@Properties\relax
224 \else\if#1A%

```


Now we use the keywords to catch `Margin`, `Style`, etc., which are not treated like `Margin2`, `Style5`, etc. If the parameter is `Margin`, for instance, we check whether the value is a correct dimension (tests are described in the next section), and in case it is, we launch `\el@GenericDef{Margin}{#2}`, which defines `\Margin1`, `\Margin2`, etc., with the value as their definition.

```

225 \else\ifx\el@TempParameter\el@MarginTest
226   \expandafter\el@UnitSearch#2?
227   \ifDubiousFigure
228     \el@DimenError{#1}{#2}%
229   \else
230     \el@GenericDef{Margin}{#2}%
231   \fi

```

`Progressive(*)`, `Indent`, `Space(*)` and `FinalSpace` behave like `Margin` and test dimensions:

```

232 \else\ifx\el@TempParameter\el@ProgressiveTest
233   \expandafter\el@UnitSearch#2?%
234   \ifDubiousFigure
235     \el@DimenError{#1}{#2}%
236   \else
237     \el@ProgressiveMargin{#2}%
238   \fi
239 \else\ifx\el@TempParameter\el@ProgressiveStarTest
240   \expandafter\el@UnitSearch#2?%
241   \ifDubiousFigure
242     \el@DimenError{#1}{#2}%
243   \else
244     \el@ProgressiveMargin*{#2}%
245   \fi
246 \else\ifx\el@TempParameter\el@IndentTest
247   \expandafter\el@UnitSearch#2?%
248   \ifDubiousFigure
249     \el@DimenError{#1}{#2}%
250   \else
251     \el@GenericDef{Indent}{#2}%
252   \fi
253 \else\ifx\el@TempParameter\el@SpaceTest
254   \expandafter\el@UnitSearch#2?%
255   \ifDubiousFigure
256     \el@DimenError{#1}{#2}%
257   \else
258     \el@GenericDef{Space}{#2}%
259   \fi
260 \else\ifx\el@TempParameter\el@SpaceStarTest
261   \expandafter\el@UnitSearch#2?%
262   \ifDubiousFigure
263     \el@DimenError{#1}{#2}%
264   \else
265     \el@GenericDef[*]{Space}{#2}%
266   \fi
267 \else\ifx\el@TempParameter\el@FinalSpaceTest
268   \expandafter\el@UnitSearch#2?%
269   \ifDubiousFigure
270     \el@DimenError{#1}{#2}%
271   \else
272     \el@GenericDef{FinalSpace}{#2}%
273   \fi

```

Hide tests whether its argument is a number. (If you don't understand `\el@Error`, see above, where it's been defined.)

```

274 \else\ifx\el@TempParameter\el@HideTest
275   \expandafter\el@NumberCheck#2?%
276   \ifDubiousFigure

```

```

277     \el@Error{#1}{#2}{number}%
278   \else
279     \el@GenericDef{Hide}{#2}%
280   \fi

```

For `Numbers`, we check that the value is a correct number denotation, namely `a`, `r`, `R`, `l`, `L` and `z` (which will be turned into commands later on).

```

281 \else\ifx\el@TempParameter\el@NumbersTest
282   \el@LetterCheck{#2}%
283   \ifDubiousLetter
284     \el@Error
285       {#1}{#2}{number denotation}%
286   \else
287     \el@GenericDef{Numbers}{#2}%
288   \fi

```

For `Align` and `Hang`, we test whether the value is some keyword, and in the case of `Align`, if it is not a keyword, we test whether it's a dimension.

```

289 \else\ifx\el@TempParameter\el@AlignTest
290   \ifx\el@TempValue\el@Fixed
291     \el@GenericDef{Align}{fixed}%
292   \else\ifx\el@TempValue\el@Move
293     \el@GenericDef{Align}{move}%
294   \else\ifx\el@TempValue\el@False
295     \else
296       \expandafter\el@UnitSearch\el@TempValue?%
297       \ifDubiousFigure
298         \el@Error
299           [.^^J==> Admissible values are 'false', 'fixed', 'move' or a dimension]%
300           {#1}{#2}{value for 'Align'}%
301         \DubiousFigurefalse
302       \else
303         \el@GenericDef{Align}{#2}%
304       \fi
305     \fi\fi\fi
306 \else\ifx\el@TempParameter\el@HangTest
307   \ifx\el@TempValue\el@True
308     \el@GenericDef{Hang}{true}%
309   \else\ifx\el@TempValue\el@False
310     \el@GenericDef{Hang}{false}%
311   \else
312     \el@Error
313       [.^^J==> Admissible values are 'true' or 'false']%
314       {#1}{#2}{value for 'Hang'}%
315   \fi\fi

```

`Start(*)` is not allowed without specifying a number, so an error is issued if it appears without one:

```

316 \else\ifx\el@TempParameter\el@StartTest
317   \PackageError{easylist}%
318     {^^J==> 'Start' can't be used without a number, so it is ignored}{}%
319 \else\ifx\el@TempParameter\el@StartStarTest
320   \PackageError{easylist}%
321     {^^J==> 'Start*' can't be used without a number, so it is ignored}{}%

```

Finally, with `(Final)Mark`, `Style(*(*))`, and `CtrCommand`, there's not much we can test, so we just launch a generic definition and hope.

```

322 \else\ifx\el@TempParameter\el@MarkTest
323   \el@GenericDef{Mark}{#2}%
324 \else\ifx\el@TempParameter\el@FinalMarkTest
325   \el@GenericDef{FinalMark}{#2}%
326 \else\ifx\el@TempParameter\el@StyleTest

```


8.4 Parametric tests

Here are the tests used on parameter names and values in `\ListProperties` and `\el@ListProperties` (hence the bad pun that titles this section). One of them, namely `\el@NumberCheck`, has been defined at the beginning of the package because we needed it to test options. First, we need some conditionals (`\ifDubiousFigure` was defined with `\el@NumberCheck`) and temporary names:

```
362 \newif\ifDubiousLetter
363 \newif\ifDubiousParameter
364 \newif\ifDubiousNumber
365 \newif\ifPoint
366 \newif\ifSign
367
368 \def\el@Parameter{}
369 \def\el@ParameterNumber{}
370 \def\el@Void{}
```

First, `\el@DubiousParameter` is called when `\el@ListProperties` finds an undefined parameter. I use it simply to give more detailed error messages; I could have let `easylist` always prompt the same error message, but using packages with this kind of parameters, I sometime get lost with their names. So I think details are welcome in error messages, even if it's not much. Anyway, `\el@DubiousParameter` scans strings token by token until it meets a `?`. A parameter name is made of letters, numbers, and stars. This test looks for them and lumps them together. For instance, when it meets a letter, it stores it in `\el@Parameter`, which is defined as `\el@P@rameter` plus the letter, where `\el@P@rameter` has been `\let` to `\el@Parameter` beforehand (watch the `@`'s!), i.e. with its previous value.

So first, we `\let` temporary names and numbers. In case this is the first iteration, they are just empty. We also reset a conditional.

```
372 \def\el@DubiousParameter#1{%
373 \let\el@P@rameter\el@Parameter
374 \let\el@P@rameterNumber\el@ParameterNumber
375 \DubiousFigurefalse
```

In case we meet the terminator, we call the two tests that'll try the parameter and its number (described below). Otherwise, we define `\easynext` to be the command itself, so it will iterate until the question mark:

```
376 \if#1?%
377 \def\easynext{\el@ParameterNumberTest\el@ParameterTest}%
378 \else
379 \let\easynext\el@DubiousParameter
```

Now we look for letters, i.e. characters of category code 11. If we find one, we store it in `\el@Parameter`:

```
380 \ifcat#1a%
381 \edef\el@Parameter{\el@P@rameter#1}%
```

If the character is not a letter, we already test what we have collected as letters. We don't wait for the end of the sequence, otherwise `Sty7le`, for instance, would be analyzed as `Style` and `7` and we'd be forced to say that it is wrong but we don't know why. So it just makes error messages a little more efficient: `Sty` is analyzed and rejected, and then when `Sty` and `le` are concatenated, although they will pass the test, the wrong analysis cannot be undone.

```
382 \else
383 \el@ParameterTest
```

Now we look for stars and collect them into the parameter name, just like letters:

```
384 \if#1*
385 \edef\el@Parameter{\el@P@rameter#1}%
```

Finally, we analyse everything else, i.e. characters of category code 12 (or worse!) except stars. When we find such a character, we test whether it's a number:

```
386 \else
387 \el@NumberCheck#1?
```

If it's not, we can already say the parameter name is wrong, since it should contain only letters, stars, and numbers.

```
388     \ifDubiousFigure
389     \DubiousParametertrue
```

If the character is a number, we collect it in `\el@ParameterNumber`, to be tested later.

```
390     \else
391     \edef\el@ParameterNumber{\el@P@rameterNumber#1}%
```

And we close and call `\easynext`:

```
392     \fi
393     \fi
394     \fi
395 \fi\easynext}
```

Now we test what we have gathered. The following two tests output values to conditionals, which are then used at the end of `\el@ListProperties` (see above), namely whether the parameter has a bad name or a bad number or both or none.

The name of the parameter is simply compared to keywords with `\el@ParameterTest`, and if it matches with none, we fire the proper conditional. If the name matches `Progressive(*)`, we turn down bad numbers, otherwise `easylist` will see 'good name, bad number', and say 'you don't have so many counters', while actually the problem is that this parameter don't take a number. So `easylist` will see 'good name, good number', say 'something's wrong but I don't know what' and politely suggest that maybe you put a number to `Progressive`. (Sorry for the unindented conditionals.)

```
397 \def\el@ParameterTest{%
398 \ifx\el@Parameter\el@MarginTest
399 \else\ifx\el@Parameter\el@MarkTest
400 \else\ifx\el@Parameter\el@FinalMarkTest
401 \else\ifx\el@Parameter\el@NumbersTest
402 \else\ifx\el@Parameter\el@IndentTest
403 \else\ifx\el@Parameter\el@StyleTest
404 \else\ifx\el@Parameter\el@CtrStyleTest
405 \else\ifx\el@Parameter\el@ParStyleTest
406 \else\ifx\el@Parameter\el@CounterCommandTest
407 \else\ifx\el@Parameter\el@ProgressiveTest
408     \DubiousNumberfalse
409 \else\ifx\el@Parameter\el@ProgressiveStarTest
410     \DubiousNumberfalse
411 \else\ifx\el@Parameter\el@StartTest
412 \else\ifx\el@Parameter\el@StartStarTest
413 \else\ifx\el@Parameter\el@HideTest
414 \else\ifx\el@Parameter\el@SpaceTest
415 \else\ifx\el@Parameter\el@SpaceStarTest
416 \else\ifx\el@Parameter\el@HangTest
417 \else\ifx\el@Parameter\el@FinalSpaceTest
418 \else\ifx\el@Parameter\el@AlignTest
419 \else\DubiousParametertrue
420 \fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi}
```

Now we test numbers. If there is none, everything's ok, but if there's one and it's larger than the total number of counters (stored in `el@CounterTotal`), then the conditional is launched.

```
422 \def\el@ParameterNumberTest{%
423 \ifx\el@ParameterNumber\el@Void
424 \else
425     \ifnum\el@ParameterNumber>\el@CounterTotal
426     \DubiousNumbertrue
427 \fi
428 \fi}
```

8.5 Non-parametric tests

Now we test the values of the parameters (hence, once again, the bad title) before \TeX gets crazy. Indeed, if the user say, for instance, `Margin=2`, we want to disable 2 (which is not a dimension) before \TeX tries to put it where it belongs and starts complaining that there lacks a legal unit of measure. Those tests are used in `\ListProperties` and `\el@ListProperties` above.

8.5.1 Dimensions

So, first, we devise a test for dimensions. It's a token-by-token test, and that's the reason why dimensions defined with \TeX 's `\newdimen` or \LaTeX 's `\newlength` should be prefixed with `\the` (they're unreadable otherwise). A dimension is made of at most one plus or minus sign at the beginning, numbers separated by at most one dot or comma for decimals, and two letters which form the unit's name. That's the basis on which we can build our test.

First, we define default tail:

```
430 \def\el@UnitSearch#1{%
431 \let\easynext\el@UnitSearch
```

Then we look for the plus or minus sign. It's ok if we have never encountered one before, in which case the dimension is wrong and we let the test gobble the rest of the sequence.

```
432 \if#1-%
433   \ifSign
434     \DubiousFiguretrue
435     \def\easynext##1?{\relax}%
436   \else
437     \Signtrue
438   \fi
439 \else
440   \if#1+%
441     \ifSign
442       \DubiousFiguretrue
443       \def\easynext##1?{\relax}%
444     \else
445       \Signtrue
446     \fi
```

If the character is not a plus minus sign, then none can appear later: the signs are always at the beginning of a dimension. Thus, as soon as we meet a character which is not a plus or minus sign, we do as if we had encountered one, i.e. with set the corresponding conditional to true.

```
447   \else
448     \Signtrue
```

Then, if we meet the terminator, it means that the dimension is wrong, since dimensions end with letters (the unit) and if letters are met, another test is launched which goes to the end of the sequence (and the terminator). So `\el@UnitSearch` should never see `?` with a valid dimension. (We use `\DubiousFiguretrue`, although we're testing dimensions, because that single conditional is enough. We don't need one for numbers, one for units, etc. As long as something is wrong, the dimension is wrong, and I think the user can find out what, contrary to the parametric tests above that were more detailed.)

```
449   \if#1?%
450     \DubiousFiguretrue
451     \let\easynext\relax
```

Next, if we meet a point or a comma, it's ok unless we already met once, in which case the dimension is wrong, and we simply gobble the rest of the sequence:

```
452   \else
453     \if#1.%
454       \ifPoint
455         \DubiousFiguretrue
456         \def\easynext##1?{\relax}%
457       \else
458         \Pointtrue
```

```

459     \fi
460   \else
461     \if#1,%
462     \ifPoint
463       \DubiousFiguretrue
464       \def\easynext##1?{\relax}%
465     \else
466       \Pointtrue
467     \fi

```

If we find a letter, we quit `\el@UnitSearch` for another test.

```

468     \else
469       \ifcat#1a%
470       \def\easynext{\el@UnitCheck#1}%

```

Now, if the character is none of the above, then its category code is 12. So we test whether it's a number:

```

471     \else
472       \el@NumberCheck#1?%

```

If it's not, that doesn't mean that the dimension is wrong. Indeed, if it is a \TeX or \LaTeX dimension as defined above, then its prefixing with `\the` turned it into a readable sequence of characters, but they all have category code 12, even letters. So the unit (which is always `pt`) can't be detected by `\ifcat#1a` above, for the `p` is not of the same category anymore. So we run a special test:

```

473       \ifDubiousFigure
474       \def\easynext{\el@DimenUnitCheck#1}%

```

And we close. The rest is up to the tests that have been called.

```

475     \fi
476   \fi
477 \fi
478 \fi
479 \fi
480 \fi
481 \fi\easynext}

```

Before testing units, we need keywords, namely their names. I hope I didn't miss one²:

```

483 \def\el@Em{em}
484 \def\el@Ex{ex}
485 \def\el@Centimetre{cm}
486 \def\el@Millimetre{mm}
487 \def\el@Inch{in}
488 \def\el@Pica{pc}
489 \def\el@Point{pt}
490 \def\el@Didot{dd}
491 \def\el@Cicero{cc}
492 \def\el@BigPoint{bp}
493 \def\el@ScaledPoint{sp}

```

Now we simply compare what we've found to those keywords. `\el@UnitCheck` takes the rest of the sequence (from the first letter found with `\el@UnitSearch`) as its argument. In case nothing matches, then the dimension is wrong (when fed with two commands, `\ifx` tests whether they have the same expansion).

```

495 \def\el@UnitCheck#1?{%
496 \def\el@TempUnit{#1}%
497 \ifx\el@TempUnit\el@Em
498 \else\ifx\el@TempUnit\el@Ex

```

²Actually, I missed those same dimensions prefixed with `true` (see the *TeXbook*, chapter 10), but since there might be any number of spaces, including zero, between `true` and the unit, it's hard to test. And I think `true` is hardly used—and one can still define the appropriate dimension beforehand. What, me, reluctant?


```

533     \expandafter\gdef\csname #2\the\el@ControlCounter#1\endcsname{.3em}%
534   \else
535     \el@Error[^^J==> and #2\the\el@ControlCounter#1\space is set to 0cm.%
536     ^^J==> Note that true TeX dimensions should be prefixed with%
537     ^^J==> \string\the\space in \string\ListProperties]%
538     {#2\the\el@ControlCounter#1}{\el@TempTestable}{dimension}%
539     \expandafter\gdef\csname #2\the\el@ControlCounter#1\endcsname{0cm}%
540   \fi
541 \fi

```

Finally, we set the stage for a new iteration:

```

542   \DubiousFigurefalse
543   \el@Advance\el@ControlCounter
544   \let\easynext\el@GenericUnitSearch
545 \fi\easynext[#1]{#2}%

```

8.5.2 Number denotation

Here's a test to check that the value of `Numbers` is valid. Well, it's quite simple, it just compares letters:

```

547 \def\el@LetterCheck#1{%
548 \if#1a%
549 \else\if#1r%
550 \else\if#1R%
551 \else\if#1l%
552 \else\if#1L%
553 \else\if#1z%
554 \else\DubiousLettertrue
555 \fi\fi\fi\fi\fi\fi}

```

The generic version is exactly the same thing as `\el@GenericUnitSearch` above, so I don't comment it. It's even simpler since we don't need an argument: only one parameter uses this test.

```

557 \def\el@GenericLetterCheck{%
558 \ifnum\el@ControlCounter>\el@CounterTotal
559   \el@ControlCounter1
560   \def\easynext{\relax}%
561 \else
562   \edef\el@TempTestable{\csname Numbers\the\el@ControlCounter\endcsname}%
563   \expandafter\el@LetterCheck\el@TempTestable
564   \ifDubiousLetter
565     \PackageError{easylist}%
566     {^^J==> ‘\el@TempTestable’ is not a valid number denotation %
567     (Numbers\the\el@ControlCounter=\el@TempTestable).}%
568     ^^J==> It is ignored and those numbers will be arabic numbers}{}%
569     \expandafter\gdef\csname Numbers\the\el@ControlCounter\endcsname{a}%
570   \fi
571   \DubiousLetterfalse
572   \el@Advance\el@ControlCounter
573   \let\easynext\el@GenericLetterCheck
574 \fi\easynext}%

```

8.5.3 Numbers

Finally we devise a generic version of `\el@NumberCheck` (defined at the beginning of the package). It concerns `Hide` and `Start(*)`. The beginning is as usual:

```

576 \newcommand{\el@GenericNumberCheck}[2][ ]{%
577 \ifnum\el@ControlCounter>\el@CounterTotal
578   \el@ControlCounter1
579   \def\easynext[##1]##2{\relax}%

```

We store the value of the parameter, make sure it's not NA (the unspecified value of `Start(*)`), and run `\el@NumberCheck`:

```
580 \else
581   \edef\el@TempTestable{\csname #2\the\el@ControlCounter#1\endcsname}%
582   \ifx\el@TempTestable\el@NA
583   \else
584     \expandafter\el@NumberCheck\el@TempTestable?%
```

If something's wrong, we issue the appropriate message depending on the name of the parameter and the presence or absence of a star, redefine the command, and close as usual:

```
585   \ifDubiousFigure
586     \def\el@Name{#2}%
587     \ifx\el@Name\el@HideTest
588       \el@Error[^^J==> and no counter will be hidden for items of level \the\el@ControlCounter]%
589       {#2\the\el@ControlCounter#1}{\el@TempTestable}{number}%
590       \expandafter\gdef\csname #2\the\el@ControlCounter#1\endcsname{0}%
591     \else
592       \if#1*%
593         \el@Error[^^J==> and this counter will continue^^ its progression]%
594         {#2\the\el@ControlCounter#1}{\el@TempTestable}{counter}%
595       \else
596         \el@Error[^^J==> and this counter will continue^^ its progression]%
597         {#2\the\el@ControlCounter#1}{\el@TempTestable}{number}%
598       \fi
599       \expandafter\gdef\csname #2\the\el@ControlCounter#1\endcsname{NA}%
600     \fi
601   \fi
602 \fi
603 \DubiousFigurefalse
604 \el@Advance\el@ControlCounter
605 \let\easynext\el@GenericNumberCheck
606 \fi\easynext[#1]{#2}}%
```

8.6 Creating items

Now we can start typesetting items. First of all, we want counters to be properly reset when higher ones are stepped. So `\el@ResetCounters` sets a scratch counter to the control counter, steps it (because we're interested in those counters that are below the current one) and launch the real job.

```
608 \def\el@ResetCounters{%
609 \el@Scratch\el@ControlCounter
610 \el@Advance\el@Scratch
611 \el@@ResetCounters}
```

First, if we have done all counters, we stop.

```
613 \def\el@@ResetCounters{%
614 \ifnum\el@Scratch>\el@CounterTotal
615 \let\easynext\relax
616 \el@Scratch0
```

Otherwise, we set the counters under investigation to 0, conditionally reset its `Start` value to NA and reiterate. Resetting `Start` just forces the user to define this parameter before an item containing that counter, which is just security. But we don't want this to happen with an intermediate counter. Indeed, setting for instance the first counter to 10 just before an item of the *second* level needs to reset the second counter, except when that counter has also just been specified with `Start2`. Now, when building an item's number, `\el@CounterLevel` represents its level (in our example, it's 2) and `\el@ControlCounter` represents the counter we're currently working with (here, 1). So the conditional does the job: it resets the second counter but not its `Start` value, in case there is one.

```
617 \else
618 \setcounter{List\the\el@Scratch}{0}%
```

```

619 \ifnum\el@ControlCounter=\el@CounterLevel
620 \expandafter\gdef\csname Start\the\el@Scratch\endcsname{NA}%
621 \fi
622 \el@Advance\el@Scratch
623 \let\easynext\el@@ResetCounters
624 \fi\easynext}

```

We need some simple definitions, including a font definition for Zapf's Dingbats.

```

626 \def\el@ItemCounter{}
627 \def\el@NA{NA}
628 \font\el@ZapfDingbats=pzdr

```

Now, here's the command that handles numbers and their punctuation. It defines `\el@ItemCounter`, to be inserted in the final product. The commands before match the `Numbers` parameter with L^AT_EX commands.

```

630 \expandafter\def\csname el@NumberDenotation:a\endcsname{\arabic}%
631 \expandafter\def\csname el@NumberDenotation:l\endcsname{\alph}%
632 \expandafter\def\csname el@NumberDenotation:L\endcsname{\Alph}%
633 \expandafter\def\csname el@NumberDenotation:r\endcsname{\roman}%
634 \expandafter\def\csname el@NumberDenotation:R\endcsname{\Roman}%
635 \expandafter\def\csname el@NumberDenotation:z\endcsname{\el@ZapfDingbats\arabic}%
636 \def\el@PrintCounters{%

```

The definition is twofold: it prints the first numbers, and then the last one, i.e. the n th one in an item of the n th level. There are few differences. So, in case we're one of the first counters, i.e. in case `\el@ControlCounter` is lower than `\el@CounterLevel` (which basically records how many §'s we've seen), and if `Start*` for this counter is unspecified (equal to NA) but `Start` is not, then we turn that counter to the value of `Start`, set it back to NA (because we don't want the counter to be stuck to that value), and reset lower counters. Indeed, if you say `\ListProperties(Start1=5)` and then type §§, chances are you want the second counter to start at 1, don't you?

```

637 \ifnum\el@ControlCounter<\el@CounterLevel
638 \expandafter\ifx\csname Start\the\el@ControlCounter*\endcsname\el@NA
639 \expandafter\ifx\csname Start\the\el@ControlCounter\endcsname\el@NA
640 \else
641 \setcounter{List\the\el@ControlCounter}{\csname Start\the\el@ControlCounter\endcsname}%
642 \expandafter\gdef\csname Start\the\el@ControlCounter\endcsname{NA}%
643 \el@ResetCounters
644 \fi

```

And if `Start*` is *not* unspecified, first we check if the value has changed: indeed, since `Start*` is meant to follow an external counter, changing its value will affect lower counters. For instance, if the first counter follows sections, every new section increases it by one and we want the second, third, etc., counters to be reset as with any incrementing of a higher counter. So if the current value of a counter is not equal to the value of its `Start*` parameter fully expanded, we launch `\el@ResetCounters`. In any case, we set the counter to `Start*`.

```

645 \else
646 \expandafter\ifnum\csname theList\the\el@ControlCounter\endcsname=%
647 \csname Start\the\el@ControlCounter*\endcsname
648 \else
649 \el@ResetCounters
650 \fi
651 \setcounter{List\the\el@ControlCounter}{\csname Start\the\el@ControlCounter*\endcsname}%
652 \fi

```

Now, if the current counter is higher than `Hide` for the current level, we print it or rather store it in `\el@ItemCounter`, which before all stores itself, i.e. previous values of itself, so when we reiterate we retrieve everything from the previous iteration.

```

653 \ifnum\el@ControlCounter>\csname Hide\the\el@CounterLevel\endcsname
654 \xdef\el@ItemCounter{\el@ItemCounter

```

We store the counter value in a group, because if its `Numbers` parameter is `z`, we change the font, and we don't want that to spread.

```

655     \bgroup
656     \csname el@NumberDenotation:\csname Numbers\the\el@ControlCounter\endcsname\endcsname{%
657         List\the\el@ControlCounter}%
658     \egroup

```

Finally, we put the punctuation mark, close the `\el@ItemCounter` and the conditional and set the stage for tail recursion:

```

659     \csname Mark\the\el@ControlCounter\endcsname}%
660     \fi
661     \el@Advance\el@ControlCounter
662     \let\easynext\el@PrintCounters

```

Now, if we're concerned with the last counter of the item, first we increment it and reset all counters below:

```

663 \else
664     \stepcounter{List\the\el@CounterLevel}%
665     \el@ResetCounters

```

Then, as before, we check `Start` and `Start*` and act accordingly, except that we don't have to check whether `Start*` has changed, because counters are reset anyway.

```

666     \expandafter\ifx\csname Start\the\el@ControlCounter*\endcsname\el@NA
667     \expandafter\ifx\csname Start\the\el@ControlCounter\endcsname\el@NA
668     \else
669         \setcounter{List\the\el@ControlCounter}{\csname Start\the\el@ControlCounter\endcsname}%
670         \expandafter\gdef\csname Start\the\el@ControlCounter\endcsname{NA}%
671     \fi
672     \else
673         \setcounter{List\the\el@ControlCounter}{\csname Start\the\el@ControlCounter*\endcsname}%
674     \fi

```

We build `\el@ItemCounter` just the same except that if `FinalMark` is specified, we put it instead of `Mark`.

```

675     \ifnum\el@ControlCounter>\csname Hide\the\el@CounterLevel\endcsname
676     \xdef\el@ItemCounter{\el@ItemCounter
677     \bgroup
678     \csname el@NumberDenotation:\csname Numbers\the\el@ControlCounter\endcsname\endcsname{%
679         List\the\el@ControlCounter}%
680     \egroup
681     \expandafter\ifx\csname FinalMark\the\el@ControlCounter\endcsname\el@NA
682     \csname Mark\the\el@ControlCounter\endcsname
683     \else
684     \csname FinalMark\the\el@ControlCounter\endcsname
685     \fi}%
686     \fi

```

And we stop the iteration and close:

```

687     \el@ControlCounter1
688     \let\easynext\relax
689     \fi
690     \easynext}

```

Now, for the final big definition, we need two boxes, two dimensions, and a definition which is an imitation of L^AT_EX's `\@sptoken` to define a space, except that I enclosed it in a group here (since `\:` already exists). It makes `\el@Space` a space.

```

692     \newbox\el@CounterBox
693     \newbox\el@ControlBox
694     \newdimen\el@TotalMargin
695     \newdimen\el@LeftMove
696     {\def\:\{\global\let\el@Space= \}\: }

```

First, we turn # into a normal character because we'll need it in the error message, then we check whether `\elNextToken`, which has been stored by § (see the definition of the `easylist` environment below), and which represents the next character after the current §, is a space, in which case we must proceed. We reset `\el@LeftMove` (see below) and then close a group. Indeed, a group is open after each item number so that the text can have `Style**` command like `\color{red}` without affecting the rest of the text. `\begin{easylist}` has a corresponding `\begingroup` and `\end{easylist}` a `\endgroup`.

```
698 \catcode'#=12
699 \def\elCreateItem{%
700 \ifx\elNextToken\el@Space
701   \global\el@LeftMove=0pt%
702   \endgroup
```

Now, if `\el@CounterLevel`, which is incremented each time a § is followed by another § and which records the level of the item we're building, is higher than the total number of counters asked for, we issue an error message (with the proper symbol, hence the ugly conditional) and replace the item number by boxed exclamation marks. (`^^b6` is § and `^^a7` is ¶; this denotation makes the package compatible with Lua_{TEX}, and it is due to Élie Roux.)

```
703 \ifnum\el@CounterLevel>\el@CounterTotal
704   \PackageError{easylist}{^^J==> Too many %
705   \ifAmpersand&\else\ifAt @\else\ifPilcrow^^b6\else\ifSharp#\else^^a7\fi\fi\fi\fi's.%
706   ^^J==> You can't use more than \the\el@CounterTotal\space
707   \ifAmpersand&\else\ifAt @\else\ifPilcrow^^b6\else\ifSharp#\else^^a7\fi\fi\fi\fi's%
708   ^^J==> unless you specify it when calling the package}{ }
709   \par\noindent\fbbox{!!!}\begingroup
```

If everything's okay, we create a paragraph and add `Space` or `Space*` depending on the level of the previous item, which was stored in `\el@PreviousItem` (0 means that there was no previous item).

```
710 \else
711   \par
712   \expandafter\ifnum\el@PreviousItem=0%
713   \else
714     \expandafter\ifnum\el@PreviousItem=\el@CounterLevel
715     \vskip\csname Space\the\el@CounterLevel*\endcsname
716     \else
717     \vskip\csname Space\the\el@CounterLevel\endcsname
718     \fi
719   \fi
```

Then we launch `\el@PrintCounters` to create `\el@ItemCounter`, and set the working margin to the value of `Margin` for the current level.

```
720 \el@PrintCounters
721 \el@TotalMargin\csname Margin\the\el@CounterLevel\endcsname
```

Now we build a box with the counter in full regalia, i.e. nested in its `CtrCom`, accompanied by its `Style(*)` and with the `FinalSpace` added at the end of it if not all counters were hidden (since if there's no counter, you don't want a space). The inner pair of braces creates a group that will prevent `Style(*)` values like `\color{blue}` from spreading to the text item.

```
722 \setbox\el@CounterBox=\hbox{%
723   \csname CtrCom\the\el@CounterLevel\endcsname{%
724     \csname Style\the\el@CounterLevel\endcsname
725     \csname Style\the\el@CounterLevel*\endcsname
726     \el@ItemCounter}%
727   \ifnum\el@CounterLevel>\csname Hide\the\el@CounterLevel\endcsname
728     \hskip\csname FinalSpace\the\el@CounterLevel\endcsname
729   \fi}}%
```

Now we have to checked the `Align` parameter. If it is `false`, we do nothing, of course. If it is set to `fixed`, we store the width of the box we've just built, and it will serve as our reference width for this level. We turn `Align` to `alreadyfixed` for items to come.

```

730 \expandafter\ifx\csname Align\the\el@CounterLevel\endcsname\el@False
731 \else\expandafter\ifx\csname Align\the\el@CounterLevel\endcsname\el@Fixed
732 \expandafter\xdef\csname CounterBoxWidth\the\el@CounterLevel\endcsname{%
733 \the\wd\el@CounterBox}%
734 \expandafter\gdef\csname Align\the\el@CounterLevel\endcsname{alreadyfixed}%

```

If `Align` is `alreadyfixed`, we rebuild the box, this time setting its width to the reference width and replacing `FinalSpace` with a glue.

```

735 \else\expandafter\ifx\csname Align\the\el@CounterLevel\endcsname\el@AlreadyFixed
736 \setbox\el@CounterBox=\hbox to \csname CounterBoxWidth\the\el@CounterLevel\endcsname{%
737 \csname CtrCom\the\el@CounterLevel\endcsname{%
738 \csname Style\the\el@CounterLevel\endcsname
739 \csname Style\the\el@CounterLevel*\endcsname
740 \el@ItemCounter}%
741 \hfil}}%

```

We copy that new box into `\el@ControlBox` to get the *real* width of the counter, compare it to the desired value, and if it is larger, we issue a warning (but use the box anyway):

```

742 \setbox\el@ControlBox=\hbox{\unhcopy\el@CounterBox}%
743 \expandafter\ifdim\wd\el@ControlBox>\csname CounterBoxWidth\the\el@CounterLevel\endcsname
744 \PackageWarning{easylist}{%
745 ^^J==> This counter is too wide and will spread on%
746 ^^J==> the item text. You should increase FinalSpace%
747 ^^J==> if you use ‘fixed’ or increase the dimension%
748 ^^J==> if you specified one.
749 ^^J==>}%
750 \fi

```

If `Align` is `move`, we store the width of the box once again and set `Align` to `alreadymoved`.

```

751 \else\expandafter\ifx\csname Align\the\el@CounterLevel\endcsname\el@Move
752 \expandafter\xdef\csname CounterBoxWidth\the\el@CounterLevel\endcsname{%
753 \the\wd\el@CounterBox}%
754 \expandafter\gdef\csname Align\the\el@CounterLevel\endcsname{alreadymoved}%

```

And if `Align` is `alreadymoved`, we set a dimension to the width of the current box minus the desired width, i.e. we determine the extra space, which we’ll remove when we insert the box.

```

755 \else\expandafter\ifx\csname Align\the\el@CounterLevel\endcsname\el@AlreadyMoved
756 \el@LeftMove=\wd\el@CounterBox
757 \advance\el@LeftMove by -\csname CounterBoxWidth\the\el@CounterLevel\endcsname

```

Finally, if `Align` is none of the above, it should be a dimension. But we have to be sure of this, so we run `\el@UnitSearch`, and if it’s ok, we rebuild the box with the dimension, which we store, and turn `Align` to `alreadyfixed`. We measure the width one again and issue a warning if the box is overfull.

```

758 \else
759 \edef\el@TempTestable{\csname Align\the\el@CounterLevel\endcsname}%
760 \DubiousFigurefalse
761 \Signfalse
762 \Pointfalse
763 \expandafter\el@UnitSearch\el@TempTestable?%
764 \ifDubiousFigure
765 \el@Error
766 [.^^J==> Admissible values are ‘false’, ‘fixed’, ‘move’ or a dimension]%
767 {Align\the\el@CounterLevel}{\csname Align\the\el@CounterLevel\endcsname}%
768 {value for ‘Align’}%
769 \expandafter\gdef\csname Align\the\el@CounterLevel\endcsname{false}%
770 \else
771 \expandafter\xdef\csname CounterBoxWidth\the\el@CounterLevel\endcsname{%
772 \csname Align\the\el@CounterLevel\endcsname}%
773 \setbox\el@CounterBox=\hbox to \csname CounterBoxWidth\the\el@CounterLevel\endcsname{%
774 \csname CtrCom\the\el@CounterLevel\endcsname{%

```

```

775         \csname Style\the\el@CounterLevel\endcsname%
776         \csname Style\the\el@CounterLevel*\endcsname%
777         \el@ItemCounter}%
778         \hfil}}%
779     \expandafter\gdef\csname Align\the\el@CounterLevel\endcsname{alreadyfixed}%
780     \setbox\el@ControlBox=\hbox{\unhcopy\el@CounterBox}%
781     \expandafter\ifdim\wd\el@ControlBox>\csname CounterBoxWidth\the\el@CounterLevel\endcsname
782     \PackageWarning{easylist}{%
783         ^^J==> This counter is too wide and will spread on%
784         ^^J==> the item text. You should increase FinalSpace%
785         ^^J==> if you use 'fixed' or increase the dimension%
786         ^^J==> if you specified one.
787         ^^J==>}%
788     \fi
789     \fi
790     \fi\fi\fi\fi\fi

```

Now we have to deal with the `Hang` parameter. If it is on, in case we're in a `alreadymoved` situation, we add the reference width to the working margin and subtract it from `\parindent`; in any other case, we do the same with the current width of the box (which is the same of the desired width if `Align` is `alreadyfixed`). The net effect of this is to leave room for the item number in the left margin and to move the first line (with `\parindent`) on the left by its width.

```

791     \expandafter\ifx\csname Hang\the\el@CounterLevel\endcsname\el@True
792     \expandafter\ifx\csname Align\the\el@CounterLevel\endcsname\el@AlreadyMoved
793     \advance\el@TotalMargin by \csname CounterBoxWidth\the\el@CounterLevel\endcsname
794     \parindent=-\csname CounterBoxWidth\the\el@CounterLevel\endcsname
795     \else
796     \advance\el@TotalMargin by \wd\el@CounterBox
797     \parindent=-\wd\el@CounterBox
798     \fi

```

If `Hang` is turned off, we simply set `\parindent` to value specified by the user:

```

799     \else
800     \parindent=\csname Indent\the\el@CounterLevel\endcsname
801     \fi

```

Finally, we set the left margin, and with `\hangafter0` we tell \TeX to start indenting from the first line on. Then we add the negative space (set to `0pt` if `Align` is not `alreadymoved`) and release the box. The `\if@afterindent` conditional is set to `true` to prevent \LaTeX from removing indentation after section titles.

```

802     \@afterindenttrue
803     \hangafter0\hangindent\el@TotalMargin
804     \hskip-\el@LeftMove\box\el@CounterBox

```

We're done with the counter and we must now set the stage for the item text. First, we open a group for the reason above, set `\@currentlabel` (used by \LaTeX to know what should be `\label`'ed with `\label`) to `\el@ItemCounter` and clear the latter (since it recursively defines itself, see above).

```

805     \begingroup
806     \edef\@currentlabel{\el@ItemCounter}%
807     \gdef\el@ItemCounter{}%

```

We shape the paragraphs to come by setting `\parindent` to the value issued by the user (since the first paragraph has already begun with the printing of the counter, hanging items won't be affected) and by repeating the margin with `\everypar` (since `\hangafter` and `\hangindent` are reset after each paragraph). And, of course, we issue the `Style(**)` of this level.

```

808     \parindent=\csname Indent\the\el@CounterLevel\endcsname
809     \everypar{\hangafter0\hangindent\el@TotalMargin}%
810     \csname Style\the\el@CounterLevel\endcsname
811     \csname Style\the\el@CounterLevel**\endcsname

```

Finally, we set some values, simply increment the level counter if there was no space after all, close by ignoring spaces so that the distance from the counter to the text will be rigidly fixed by `FinalSpace`, and restore #.

```

812   \fi
813   \xdef\el@PreviousItem{\the\el@CounterLevel}%
814   \global\el@CounterLevel1
815 \else
816   \global\el@Advance\el@CounterLevel
817 \fi\ignorespaces}
818 \catcode'#=6

```

Here are the predefined styles. There's nothing much to comment. `\elPredefinedStyle` is called by `\begin{easylist}` and does nothing if nothing follows.

```

820 \def\el@Tractatus{tractatus}
821 \def\el@CheckList{checklist}
822 \def\el@BookToc{booktoc}
823 \def\el@ArticleToc{articletoc}
824 \def\el@Enumerate{enumerate}
825 \def\el@Itemize{itemize}
826
827 \def\elPredefinedStyle{\@ifnextchar[{\el@PredefinedStyle}{}]}
828
829 \def\el@PredefinedStyle[#1]{%
830 \def\el@TempStyle{#1}%
831 \ifx\el@TempStyle\el@Tractatus
832   \NewList(Mark=,Mark1=.)%
833 \else\ifx\el@TempStyle\el@CheckList
834   \NewList(%
835     Hide=1000,Progressive*=1em,Hang=true,%
836     Style*={\framebox(7,7){}}\hskip.6em,
837     Style1*=\bfseries)
838 \else\ifx\el@TempStyle\el@BookToc
839   \NewList(%
840     Hang=true,FinalMark=,Hide=1,%
841     Style1=\large\bfseries,Numbers1=R,Space1=2.25em,Space1*=2.25em,Hide1=0,Hang1=false,Align1=2em,%
842     Style2=\bfseries,Space2=1em,Space2*=1em,Align2=1.5em,%
843     Margin3=1.5em,Margin4=3.8em,Margin5=7em,Margin6=10em,Margin7=12em,%
844     Align3=2.3em,Align4=3.2em,Align5=4.1em,Align6=5em,Align7=6em)%
845 \else\ifx\el@TempStyle\el@ArticleToc
846   \NewList(%
847     Hang=true,FinalMark=,%
848     Align1=1.5em,Style1=\bfseries,Space1=1em,Space1*=1em,%
849     Margin2=1.5em,Margin3=3.8em,Margin4=7em,Margin5=10em,%
850     Align2=2.3em,Align3=3.2em,Align4=4.1em,Align5=5em)%
851 \else\ifx\el@TempStyle\el@Enumerate
852   \NewList(%
853     FinalSpace=.5em,Hang=true,Mark=.,Space=4pt,Space*=4pt,Align=move,%
854     Margin1=1.2em,%
855     Margin2=2.9em,Style2*={(),Mark2={}},Numbers2=1,Hide2=1,%
856     Margin3=5.6em,Numbers3=r,Hide3=2,%
857     Margin4=6.8em,Numbers4=L,Hide4=3)%
858 \else\ifx\el@TempStyle\el@Itemize
859   \NewList(%
860     Hang=true,Space=4pt,Space*=4pt,Hide=1000,%
861     Margin1=1.5em,Style1*=\textbullet\hskip.5em,%
862     Margin2=3.7em,Style2*=-\hskip.5em,%
863     Margin3=5.9em,Style3*=\ast\hskip.5em,%
864     Margin4=7.8em,Style4*=\cdot\hskip.5em)%
865 \else
866   \PackageError{easylist}{^~J==> '\el@TempStyle' is not a valid predefined style}{}%
867 \fi\fi\fi\fi\fi\fi}

```


Finally, we define the environment. First we turn off @ and store the category codes of the symbols to be made active. I could have simply said for instance `\catcode'#=6` but who knows, catcodes might have been changed by a previous package. `\edef\AtCatcode{\number\catcode'@\relax}` is useless since we just said `\makeatletter`, but it's for the sake of symmetry.

```

869 \makeatother
870
871 \edef\SectionCatcode{\number\catcode'~a7}
872 \edef\PilcrowCatcode{\number\catcode'~b6}
873 \edef\SharpCatcode{\number\catcode'#}
874 \edef\AtCatcode{\number\catcode'@}
875 \edef\AmpersandCatcode{\number\catcode'&}

```

Then we make them active to allow a definition that will make them, say, active.

```

877 \catcode'~a7=\active
878 \catcode'~b6=\active
879 \catcode'@=\active
880 \catcode'#=\active
881 \catcode'&=\active

```

Now, according to the option loaded with the package, we create the proper environment. For instance, if @ was chosen, we make it active in the environment and defines it as follows: it stores the next item in `\elNextToken` and calls `\elCreateItem`, which will act accordingly.

```

883 \ifAt
884 \def\easylist{%
885 \catcode'@=\active
886 \def@{\futurelet\elNextToken\elCreateItem}%

```

Next `\easylist` opens a group to match those created by items and launch `\elPredefinedStyles`, while `\endeasylist` closes a group and add a `\par` that will ensure that the last item of an `easylist` is properly formatted.

```

887 \begingroup\elPredefinedStyle}
888 \def\endeasylist{\endgroup\par}

```

Finally we define `\Activate` and `\Deactivate`, which are straightforward. `\AtCatcode` is `\xdef`'ed because we want the current value category code of @, and `\Activate` might be issued in a group, so we want `\AtCatcode` to be global.

```

889 \gdef\Activate{%
890 \xdef\AtCatcode{\number\catcode'@}%
891 \catcode'@=\active}
892 \gdef\Deactivate{\catcode'@=\AtCatcode}

```

And we do the same for the other symbols:

```

893 \else
894 \ifPilcrow
895 \def\easylist{%
896 \catcode'~b6=\active
897 \def~b6{\futurelet\elNextToken\elCreateItem}%
898 \begingroup\elPredefinedStyle}
899 \def\endeasylist{\endgroup\par}
900 \gdef\Activate{%
901 \xdef\PilcrowCatcode{\number\catcode'~b6}%
902 \catcode'~b6=\active}
903 \gdef\Deactivate{\catcode'~b6=\PilcrowCatcode}
904 \else
905 \ifSharp
906 \def\easylist{%
907 \catcode'#=\active
908 \def#{\futurelet\elNextToken\elCreateItem}%
909 \begingroup\elPredefinedStyle}
910 \def\endeasylist{\endgroup\par}

```

```

911     \gdef\Activate{%
912     \xdef\SharpCatcode{\number\catcode'#}%
913     \catcode'#=\active}
914     \gdef\Deactivate{\catcode'#=\SharpCatcode}
915     \else
916     \ifAmpersand
917     \def\easylist{%
918     \catcode'&=\active
919     \def&{\futurelet\elNextToken\elCreateItem}%
920     \begingroup\elPredefinedStyle}
921     \def\endeasylist{\endgroup\par}
922     \gdef\Activate{%
923     \xdef\AmpersandCatcode{\number\catcode'&}%
924     \catcode'&=\active}
925     \gdef\Deactivate{\catcode'&=\AmpersandCatcode}
926     \else
927     \def\easylist{%
928     \catcode'^a7=\active
929     \def^a7{\futurelet\elNextToken\elCreateItem}%
930     \begingroup\elPredefinedStyle}%
931     \def\endeasylist{\endgroup\par}
932     \gdef\Activate{%
933     \xdef\SectionCatcode{\number\catcode'^a7}%
934     \catcode'^a7=\active}
935     \gdef\Deactivate{\catcode'^a7=\SectionCatcode}
936     \fi
937     \fi
938     \fi
939     \fi

```

At last, we restore the original catcodes and say goodbye.

```

941 \catcode'&=\AmpersandCatcode
942 \catcode'#=\SharpCatcode
943 \catcode'@=\AtCatcode
944 \catcode'^b6=\PilcrowCatcode
945 \catcode'^a7=\SectionCatcode

```